EXPEDITION SE

// WHAT'S NEW

• Large panoramic 7.8-in. wide LCD color display available • HPG front and center shocks

// PACKAGE HIGHLIGHTS

- Rotax° 600R E-TEC°, 900 ACE™ Turbo and 900 ACE™ engines
- pDrive™ clutch
- REV® Gen4 platform with wide-design bodywork
- 20-in. wide Multi-LinQ plate with 125 lb / 56.7 kg cargo capacity
- SC $^{\text{\tiny{M}}}$ -5U articulating rear suspension with locking mechanism on one side (no tool required)
- Air Control Suspension (ACS)
- 20 x 154 track choices: 1.5 in. Silent Cobra WT or Silent Ice Cobra WT or 1.8 in. Cobra WT
- · Air radiator with fan
- RF D.E.S.S.™ key

Front suspension

Front suspension travel Rear suspension

Front shock

Center shock

Rear Shock Rear suspension travel

• Easy Shift transmission (H-L-N) with RER™ electronic reverse • Heated driver's visor power outlet (600R E-TEC) / electro-mechanical reverse (ACE™ engines)

- Removable passenger seat and with heated grips
- Ultra large LinQ utility cargo box with 135 L / 35.7 US gal of storage
- Hitch receiver with 1,500 lb / 680 kg towing capacity when equiped with an HD rear bumper (1,200 lb / 544 kg std.)
- High capacity battery
- Forward Adjustable Riser
- Gauge choices: 7.2-in. wide digital display or Large panoramic 7.8-in. wide LCD color display
- 27.5-in. Ultra-high windshield with side deflectors
- Deep snow running boards with large openings



EXPEDITION° SE 900 ACE™ TURBO SHOWN

// EXTRA HIGHLIGHTS

900 ACE™ TURBO & 900 ACE™ WITH 650W MAGNETO

- Reversible throttle lever (thumb or finger activated) iTC[™] Engine mapping modes (Standard, Sport or ECO[®])
- · Engine oil cooler

RAS™ 3

HPG™ 210 mm / 8.3 in.

SC™-5U

HPG™

ACS (Air Control Suspension)

239 mm / 9.4 in.

· High efficiency air radiator with fan

ROTAX° ENGINE	600R E-TEC°	900 ACE™ Turbo	900 ACE™
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3	3
Displacement	599.4 cc / 36.6 in.3	899 cc / 54.9 in.3	899 cc / 54.9 in.3
Bore	72.3 mm / 2.85 in.	74 mm / 2.9 in.	74 mm / 2.9 in.
Stroke	73 mm / 2.87 in.	69.7 mm / 2.7 in.	69.7 mm / 2.7 in.
Maximum engine speed	8,100 RPM	7,300 RPM	7,250 RPM
Carburation	E-TEC direct injection	EFI	EFI
Recommended fuel type	Premium unleaded	Premium unleaded	Regular unleaded
Minimum octane	91	91	87
Fuel tank	36 L / 9.5 US gal	42 L / 11.1 US gal	42 L / 11.1 US gal
Dil tank capacity	3.4 L / 3.6 qt	3.3 L / 3.5 qt	3.3 L / 3.5 qt
DRY WEIGHT	290 kg / 639 lb	315 kg / 694 lb	301 kg / 663 lb
POWERTRAIN			
Drive clutch type	pDrive™	pDrive™	pDrive™ with slider shoe
Driven clutch type	QRS	QRS	QRS
Engagement	3,400 RPM	2,000 RPM	2,200 RPM
Small sprocket number of teeth	Lo = 3.87:1 ratio	Lo = 3.59:1 ratio	Lo = 4.24:1 ratio
Large sprocket number of teeth	Hi = 2.15:1 ratio	Hi = 2.0:1 ratio	Hi = 2.36:1 ratio
Drive sprocket number of teeth	8	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.	183 mm / 7.2 in.
Drive sprocket pitch	73 mm / 2.86 in.	73 mm / 2.86 in.	73 mm / 2.86 in.
Brake system	Brembo brake with	Brembo brake with d stainless-steel braided	Brembo brake with stainless-steel braided

COLOR

Lava Red / Black		
DIMENSIONS		
Vehicle overall length	3,256 mm / 128.2 in.	
Vehicle overall width	1,200 to 1,240 mm / 47.7 to 48.8 in.	
Vehicle overall height	1,513 mm / 59.6 in.	
Ski stance	975 or 1,020 mm / 38.4 or 40.2 in.	
Track (Length x Width x Profile)	Silent Cobra WT: 154 x 20 x 1.5 in. [3,923 x 500 x 38 mm] Silent Ice Cobra WT: 154 x 20 x 1.5 in. [3,923 x 500 x 38 mm] opt. Cobra WT: 154 x 20 x 1.8 in. [3,923 x 500 x 46 mm] opt.	

FEATURES

Frame	REV° Gen4	
Bodywork	Wide design	
Skis	Pilot™ 7.4	
Seating	2-up modular with underseat storage	
Handlebar	U-shaped aluminum with J-hooks / Low grab handle	
Riser block height	Adjustable-120 mm / 4.7 in.	
Starter	Electric	
Reverse	RER™ (600R E-TEC°) Electro-mechanic (ACE™ engines)	
Heated throttle lever / grips	Standard (driver and passenger)	
Gauge type	7.2-in. wide digital display 7.8-in. wide LCD color display (opt.)	
Windshield	673 mm / 27.5 in. with mirrors	
Runner	Square 3/8	
Carbide configuration	102 mm / 4 in. at 90°	
Bumpers (Front/Rear)	Heavy Duty / Hitch receiver	



EXPEDITION° SE 900 ACE™ TURBO SHOWN

// FEATURE HIGHLIGHTS



Rotax® 900 ACE™ Turbo engine

With a Rotax-built turbocharger specifically designed for the 900 ACE engine, riders get the technology they love with the reliable, powerful performance they demand in one advanced engine package.



Multi-Lin0 plate

Standard LinQ adaptable storage. Fits 16- and 20-inch-wide LinQ accessories to maximize accessory options. Up to 125 lb (56.7 kg) cargo capacity.



Easy Shift transmission (H-L-N) with push-button reverse

Easily shifts with multiple gear ratios. Built for heavy duty reliability with high load resistance and optimal lubrication. Handlebar push-button engages reverse - electronic RER™ with E-TEC engine choice, electromechanical with ACE™ engines.



Large panoramic 7.8 in. Wide LCD Color Display available

Wide screen full-color display lets riders truly customize their ride from behind the bars. Choose your preferred sled info, and see app integrated information in a split-screen format with GPS. Bluetooth music. helmet-to-helmet communication and more



Ultra large LinQ utility cargo box

135 L / 35.7 US gal of lockable, weather resistant storage capacity. Incorporated hatchet and saw holder, plus attachment points for bungees and two 16-in. LinQ positions on top for expandable accessory use.



SC™-5U articulating rear suspension

Features settings that maximize deep snow traction in reverse or lock out for towing.





©2020 Bombardier Recreational Products Inc., [BRP]. All rights reserved. ™,® and the BRP logo are trademarks of BRP or its affiliates. Products are distributed in the USA by BRP US Inc. 'All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring