

MY24 MAVERICK DS TURBO RR



Catalyst Gray

ENGINE	
Type	149 kW (200 hp*), Rotax® ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTCTM) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 2WD/4WD with front diff. lock / 4WD TRAIL ACTIV/ 4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 20 in. (50.8 cm) travel
Front Shocks	SHOWA HPG piggyback 2.5 (Dual Speed Compression, Dual-rate spring)
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar / 20 in. (50.8 cm) travel
Rear Shocks	SHOWA HPG piggyback 2.5 (Dual Speed Compression, Dual-rate spring)

TIRES / WHEELS	
Front & Rear Tires	Maxxis Carnivore† 30 x 10 / 10 x 14 in. (76.2 x 25.4 / 25.4 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

HIGHLIGHTS	
• Smart-Lok™ front differential	
• SHOWA HPG piggyback 2.5 shocks	
• High torque Dynamic Power Steering (DPS)	
• Belt monitoring system	
• 850 W Magneto	
• 14 in. (35.6 cm) cast-aluminum wheels	
• 30 in. (76.2 cm) Maxxis Carnivore† tires	
• 4.5 in. (11.4 cm) digital display with keypad	
• Rear tow hook	
• Horn & Buzzer	

DIMENSIONS / CAPACITIES	
Estimated Dry Weight **	1,546 lb (701.3 kg)
Chassis / Cage	Dual-phase 980 steel
L x W x H	132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES	
Gauge	4.5 in. (11.4 cm) wide digital display with keypad
Instrumentation	DC Outlet (10-A)
Magneto	850 W
Ignition	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights LED tail lights
Winch	N/A
Protection	Integrated front bumper Quarter-doors HMWPE full skid plate Rear tow hook

WARRANTY	
Factory warranty	2-year BRP limited warranty

*149kw/200hp based on MY22 U.S. EPA certification, or 145kw/195hp based on current EU NRMM certification.



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. **Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.



REQUEST A QUOTE

